

Compu-Flow™

Econo-Mag

Magnetic Single Point Insertion Flow Meter

The Compu-Flow™ Econo-Mag Single Point Insertion Flow Meter is engineered with industry-leading features to deliver uncompromised flow measurement solutions for today's demanding industries.



Compu-Flow™ introduces the economical industrial-grade magnetic single point insertion flow meter for superior flow measurement: The Econo-Mag. The revolutionary new and enhanced hardware and software design results in a low-profile, high performance flow meter that delivers precise flow readings due to its advanced proprietary micro-processing technology. Stainless-steel probe with stainless-steel electrodes are mounted in teflon for extended service life. Upper housing and all hardware is either PVC or stainless-steel.

The Compu-Flow™ Econo-Mag produces a rapidly reversing magnetic field in the probe, and as the fluid moves through this field a voltage is generated. This voltage is measured and translated into a frequency signal that is proportional to flow rate. This digital signal can be sent directly to a PLC, SCADA, or can be processed using any of the Compu-Flow™ indicators or receivers. Signal cable is standard 25', optional to 1000'.

The complete lack of moving parts in the Compu-Flow™ Econo-Mag flow sensor is the source of its reliability. There is no rotor to stop turning as in dirty water and there are no bearings to wear out. Stainless and PVC materials withstand a variety of temperature, pressure, and chemical conditions. Reverse flow-output and submersible models are optional. The Econo-Mag is a stand-alone flow sensor.

The Compu-Flow™ Econo-Mag is truly Flow Smart.

Features

- **Quick & Easy Installation:** Installation time from start to finish is typically 30 minutes.
- **User-Friendly:** Engineered with an extremely easy to use interface. No math or formulas required.
- **High-performance:** Out-performs competition in accuracy and reliability. NIST Certified to < 0.5%.
- **Zero Corrosion Factor:** All exposed components; Stainless-Steel, PVC, or Polycarbonate.
- **Compu-Flow™ Smart-Flow Technology:** Proprietary technology delivers best-in-class flow readings.
- **Lightweight & Low Profile:** The Compu-Flow™ Econo-Mag is the first in its class to provide a revolutionary lightweight low profile hardware design. The future of magnetic flow meters is here. Custom probe lengths optional.
- **Multi-industry flow measurement solution:** Engineered to measure virtually all conductive water based flows.
- **Rapid Response Time:** Instant accurate flow readings. Selectable update times.
- **Economically Priced:** Engineered to be the most economically priced flow meter in its class.

Package Includes:

Fixed:

- NEMA 4X Display IP65
- Transducer & 25' cable IP68
- Power Supply
- Sensor Coupling Hardware
- Quick Start Guide
- USB Flash Drive / User Manual

Portable:

- All of the above plus:
- 12V 1.0AH AGM Battery
- 90/240 VAC/12VDC @ 1.0A Smart Charger
- Auxiliary Handle
- Field Transport Case
- Quick Connect Flow Sensor Port



Specifications:

Display:

NEMA – 4X hinged IP65
Temp: (+4°F to +140°F)

Dimensions:

7 x 5 x 3 inches

Totalizer:

12 Digit LCD
Memory Backup 99 yrs +

Rate Meter:

4 Digit LCD + Digital Bar Graph

Memory:

Non-volatile 99 yrs +
All parameter inputs

Power:

Isolated-Regulated-Module
100-240 VAC / 12VDC @ 1.0A

LED Indicators: (Receiver)

Green – Power, Yellow – Echo,
Red – Hi/Low Alarm

Outputs:

Digital Pulse Train (0-12V)
4-20mA (MAX z1200 ohm)
RS232 via DB9 Port
Hi-Low Limit Alarms * Batch Control *
* (12VDC @50mA)

Transducer:

Stainless-steel 1" probe IP68
Power: 12/24VDC @ 120mA
Submersible 200' Max
Potted IP68 Non- Metallic
Potted Temp (+4°F to +220°F)
Digital Pulse Train (0-12V)
Analog Signal 12VDC
K Factor - 100Hz/FPS

Cable Length:

25 ft. standard
0 to 2000 ft. (optional)

Flow Range:

FPS: 0-30 fps/ 10 mps
Resolution .1 fps, 0.03 mps

Pipe ID Range:

0 – 99.99 inches
0 – 2540 mm

Accuracy:

1% (function of flow profile)

Linearity:

+/- 0.5%

Repeatability:

+/- 0.1%

Options:

Wireless Signal 900 MHz
Data Logger 1- 32 GB
Flash Drive Internal or Remote
Probe lengths: 6", 12", 18", 24", 36"
Custom probe lengths available

Weight:

4 lbs. - Fixed System
8 lbs. - Portable System

Engineering Units:

English & Metric

Languages:


- English

Part Number:

CEM-100E

Warranty:

2-Year Limited Warranty



© Compu-Flow®. All rights reserved.

Rev 22.0

